


AMENDMENT TO THE CLAIMS

1. (Currently Amended) An esterified polyalkene/unsaturated acidic reagent copolymer which is the reaction product of a polyol and a copolymer of the general formula:



wherein X and X' in each repeating unit of the copolymer are independently selected from the group consisting of —OH; —O—R₃ wherein R₃ is a lower alkyl of 1 to 6 carbon atoms; or taken together are —O— to form a succinic anhydride group; n is a whole integer from 1 to 3; R₁ is a lower alkyl of 1 to 6 carbon atoms; R₂ is a polyalkyl group having about 9 to about 200 carbon atoms; m is a whole integer of from 1 to 3; x is a number greater than 1 up to 20; Int. is at least one initiating radical; and Ter. is at least one terminating group; and wherein the copolymer has a succinic ratio of about 1 and wherein the reaction product is from about 40 to about 70% esterified.

2. (Original) The esterified copolymer of Claim 1, wherein R₁ is methyl and R₂ is polyisobutyl.

3. (Original) The esterified copolymer of Claim 1, wherein R₂ is polyisobutyl having about 15 to about 100 carbon atoms.

4. (Original) The esterified copolymer of Claim 1, wherein R₂ is polyisobutyl having about 24 to about 80 carbon atoms.

5. (Original) The esterified copolymer of Claim 1, wherein R₂ is polyisobutyl having about 28 to about 50 carbon atoms.

6. (Original) The esterified copolymer of Claim 1, wherein R₂ is polyisobutyl having a number average molecular weight of about 210 to about 1400.

7. (Original) The esterified copolymer of Claim 1, wherein R₂ is polyisobutyl having a number average molecular weight of about 336 to about 1120.

8. (Original) The esterified copolymer of Claim 1, wherein R₂ is polyisobutyl having a number average molecular weight of about 350 to about 700.

9. (Original) The esterified copolymer of Claim 1, wherein the polyalkyl group is derived from a polyalkylene having at least 20 percent of an alkylvinylidene isomer.

10. (Original) The esterified copolymer of Claim 9, wherein the polyalkyl group is derived from a polyalkylene having at least 50 percent of an alkylvinylidene isomer.

11. (Original) The esterified copolymer of Claim 1, wherein X and X' taken together are —O— to form a succinic anhydride group.

12. (Original) The esterified copolymer of Claim 1, wherein the polyol is of the formula $R''(OH)_y$ wherein R'' is a hydrocarbon radical and y is an integer representing the number of hydroxy radicals and has a value of 2 to about 10.

13. (Original) The esterified copolymer of Claim 1, wherein the polyol is selected from the group consisting of ethylene glycol, di(ethylene glycol), tri(ethylene glycol), di(propylene glycol), tri(butylene glycol), penta(ethylene glycol), glycerol, pentaerythritol, 2,4-hexanediol, pinacol, erythritol, arabitol, sorbitol, mannitol, 1,2-cyclohexanediol, xylylene glycol, 1,3,5-cyclohexanetriol and mixtures thereof.

14. (Original) The esterified copolymer of Claim 1, wherein the polyol is pentaerythritol.

15. (Original) The esterified copolymer of Claim 1, having a number average molecular weight of about 600 to about 30,000.

16. (Original) The esterified copolymer of Claim 1, having a number average molecular weight of about 5,000 to about 25,000.

17. (Original) The esterified copolymer of Claim 1, having a number average molecular weight of about 10,000 to about 20,000.

18. (Original) The esterified copolymer of Claim 1, which is an alternating copolymer.

19-46. (Cancelled)

47. (Original) A lubricating oil concentrate comprising from about 10 wt.% to about 90 wt.% of the esterified copolymer of Claim 1 and from about 90 wt.% to about 10 wt.% of an oil of lubricating viscosity.

48. (Original) A lubricating oil concentrate comprising from about 10 wt.% to about 90wt.% of the esterified copolymer of Claim 5 and from about 90 wt.% to about 10 wt.% of an oil of lubricating viscosity.

49. (Original) A lubricating oil concentrate comprising from about 10 wt.% to about 90wt.% of the esterified copolymer of Claim 8 and from about 90 wt.% to about 10 wt.% of an oil of lubricating viscosity.

50-51. (Cancelled)

52. (Original) A lubricating oil composition comprising a major amount of an oil of lubricating viscosity and a friction modifying effective amount of the esterified copolymer of Claim 1.

53. (Original) A lubricating oil composition comprising a major amount of an oil of lubricating viscosity and a friction modifying effective amount of the esterified copolymer of Claim 5.

54. (Original) A lubricating oil composition comprising a major amount of an oil of lubricating viscosity and a friction modifying effective amount of the esterified copolymer of Claim 8.

55-56. (Cancelled)

57. (Original) The lubricating oil composition of Claim 52, wherein the friction modifying effective amount of the esterified copolymer is about 0.1 to about 10 wt.%.

58. (Original) The lubricating oil composition of Claim 52, wherein the friction modifying effective amount of the esterified copolymer is about 0.5 wt. % to about 5 wt. %.

59. (Original) The lubricating oil composition of Claim 52, wherein the oil of lubricating viscosity is a power transmission fluid.

60. (Original) The lubricating oil composition of Claim 53, wherein the oil of lubricating viscosity is a power transmission fluid.

61. (Original) The lubricating oil composition of Claim 54, wherein the oil of lubricating viscosity is a power transmission fluid.

62. (Original) A fuel concentrate comprising an inert stable oleophilic organic solvent boiling in the range of about 150°F to about 400°F and about 5 to about 70 wt. % of the esterified copolymer of Claim 1.

63. (Original) A fuel concentrate comprising an inert stable oleophilic organic solvent boiling in the range of about 150°F to about 400°F and about 5 to about 70 wt. % of the esterified copolymer of Claim 5.

64. (Original) A fuel concentrate comprising an inert stable oleophilic organic solvent boiling in the range of about 150°F to about 400°F and about 5 to about 70 wt. % of the esterified copolymer of Claim 8.

65. (Cancelled)

66. (Original) A fuel composition comprising a major amount of a hydrocarbon fuel and a minor friction modifying effective amount of the esterified copolymer of Claim 1.

67. (Original) A fuel composition comprising a major amount of a hydrocarbon fuel and a minor friction modifying effective amount of the esterified copolymer of Claim 5.

68. (Original) A fuel composition comprising a major amount of a hydrocarbon fuel and a minor friction modifying effective amount of the esterified copolymer of Claim 8.

69. (Cancelled)

70. (Original) The fuel composition of Claim 66, wherein the hydrocarbon fuel is a diesel fuel.

71. (Original) The fuel composition of Claim 67, wherein the hydrocarbon fuel is a diesel fuel.

72. (Original) The fuel composition of Claim 68, wherein the hydrocarbon fuel is a diesel fuel.

73. (Cancelled)

74. (Original) A method for improving the torque capacity, low temperature operability and anti-shudder durability of a power transmission lubricating oil composition which comprises adding a minor effective amount of the esterified copolymer of Claim 1 to a power transmission fluid.

75. (Original) A method for improving the torque capacity, low temperature operability and anti-shudder durability of a power transmission lubricating oil composition which comprises adding a minor effective amount of the esterified copolymer of Claim 5 to a power transmission fluid.

76. (Original) A method for improving the torque capacity, low temperature operability and anti-shudder durability of a power transmission lubricating oil composition which comprises adding a minor effective amount of the esterified copolymer of Claim 8 to a power transmission fluid.


77. (Original) A method for improving the fuel economy of a diesel engine which comprises operating the diesel engine with a fuel composition comprising (a) a major amount of a diesel fuel and (b) a minor fuel economy improving effective amount of the esterified copolymer of Claim 1.

78. (Original) A method for improving the fuel economy of a diesel engine which comprises operating the diesel engine with a fuel composition comprising (a) a major amount of

a diesel fuel and (b) a minor fuel economy improving effective amount of the esterified copolymer of Claim 5.

79. (Original) A method for improving the fuel economy of a diesel engine which comprises operating the diesel engine with a fuel composition comprising (a) a major amount of a diesel fuel and (b) a minor fuel economy improving effective amount of the esterified copolymer of Claim 8.

80. (New) An esterified polyalkene/unsaturated acidic reagent copolymer which is the reaction product of a polyol and a copolymer of the general formula:



wherein X and X' in each repeating unit of the copolymer are independently selected from the group consisting of —OH; —O—R₃ wherein R₃ is a lower alkyl of 1 to 6 carbon atoms; or taken together are —O— to form a succinic anhydride group; n is a whole integer from 1 to 3; R₁ is a lower alkyl of 1 to 6 carbon atoms; R₂ is a polyalkyl group having about 9 to about 200 carbon atoms; m is a whole integer of from 1 to 3; x is a number greater than 1 up to 20; Int. is at

least one initiating radical; and Ter. is at least one terminating group; and wherein the copolymer has a succinic ratio of about 1 and wherein the reaction product is from about 40 to about 70% esterified and has a number average molecular weight of about 5,000 to about 25,000.

81. (New) The esterified copolymer of Claim 80, having a number average molecular weight of about 10,000 to about 20,000.